



**TN 95**

- Raccordo di estremità a gomito
- Winkel-Einschraubverschraubungen
- Stud Elbows
- Coude mâle

Filettatura:  
Gas cilindrica  
Metrica cilindrica

Einschraubgewinde:  
Withworth-Rohrgewinde zylindrisch  
Metrisches Feingewinde zylindrisch

Thread  
B.S.P. parallel  
Metric parallel

Filetage:  
Gaz cylindrique  
Métrique cylindrique

Forma B DIN 3852 Foglio 2

Form B DIN 3852 Teil 2

Type B DIN 3852 Part 2

Forme B DIN 3852 Partie 2

Serie Reihe Series Série	Ø Tubo Rohr AD Tube O.D. Ø Tube d <sub>1</sub>	PN PE	I	L	L1	L3	CH1	CH2	R			M			Peso Gewicht Weight Poids kg.x100 P.
									Ø F	Ø N	Simbolo di ordinazione Bestell-Nr. - Part.No. Références	Ø F	Ø N	Simbolo di ordinazione Bestell-Nr. - Part.No. Références	
L	22	PN 160	16	44	27,5	26	36	27	3/4"	32	<b>TN 95 - 22 LR</b>	26 × 1,5	31	<b>TN 95 - 22 LM</b>	24,6
	28		18	47	30,5	30	41	36	1"	39	<b>TN 95 - 28 LR</b>	33 × 2	39	<b>TN 95 - 28 LM</b>	34,7
	35		20	56	34,5	34	50	41	1" 1/4	49	<b>TN 95 - 35 LR</b>	42 × 2	49	<b>TN 95 - 35 LM</b>	61,2
	42		22	63	40	39	60	50	1" 1/2	55	<b>TN 95 - 42 LR</b>	48 × 2	55	<b>TN 95 - 42 LM</b>	84,6
S	20	PE 400	16	48	26,5	26	36	27	3/4"	32	<b>TN 95 - 20 SR</b>	27 × 2	32	<b>TN 95 - 20 SM</b>	30,3
	25		18	54	31	30	46	36	1"	39	<b>TN 95 - 25 SR</b>	33 × 2	39	<b>TN 95 - 25 SM</b>	58,0
	30		20	62	35,5	34	50	41	1" 1/4	49	<b>TN 95 - 30 SR</b>	42 × 2	49	<b>TN 95 - 30 SM</b>	74,4
	38		22	72	41	39	60	50	1" 1/2	55	<b>TN 95 - 38 SR</b>	48 × 2	55	<b>TN 95 - 38 SM</b>	98,9

- Le dimensioni di ingombro si intendono a raccordo chiuso.
- Baumaße sind ca.-Maße bei angezogener Überwurfmutter.

- Overall sizes are with closed fitting.
- Les dimensions d'encombrement s'entendent raccord monté.