



Gerade Einschraub- Verschraubungen

Bestellzeichen: AP

Einschraubgewinde:
Whitworth-Rohrgewinde, kegelig

Einschraublöcher Kap. I

Male Stud Couplings

order code: AP

Stud thread:
B.S.P., taper

Port forms see Cap. I

Unions mâles

Référence de commande: AP

Filetage mâle:
Whitworth, conique

Voir taraudages correspondants chap. I

Rohr AD pipe OD Tube Ø ext.	PN	L ₁	L ₁	i	S	S ₁	G	kg für % ST kg for % pc. kg en %	Bestellzeichen order code Réf. cde	
6	L 315 [1260]	30	15	8	12	14	R 1/8" K	2,2	AP 6-L/R 1/8"	
8		35	20	12	17	17	R 1/4" K	3,8	AP 8-L/R 1/4"	
10		37	22	12	17	19	R 1/4" K	4,3	AP 10-L/R 1/4"	
12		37	22	12	19	22	R 3/8" K	6,0	AP 12-L/R 3/8"	
15		40	25	14	24	27	R 1/2" K	10,3	AP 15-L/R 1/2"	
18		42	25,5	14	27	32	R 1/2" K	12,7	AP 18-L/R 1/2"	
22		46	29,5	16	32	36	R 3/4" K	18,5	AP 22-L/R 3/4"	
28		160 [640]	51,5	34,5	18	41	41	R 1" K	25,8	AP 28-L/R 1"
35			56	34,5	20	50	50	R 1 1/4" K	41,5	AP 35-L/R 1 1/4"
42			61	38	22	55	60	R 1 1/2" K	56,7	AP 42-L/R 1 1/2"

Hinweise zu Druck- und Temperaturangaben siehe Seiten I/9 + I/10 / Hints concerning pressure-information – see I/9 + I/10 / Informations sur les pressions – voir I/9 + I/10
L₁ = Ungefährmaß bei angezogener Mutter / L₁ = approximate length with nut tightened / L₁ = longueur approximative, l'écrou étant bloqué