



Petroleum Transfer Hose

**Blacksnake®
(Curb Pump - Hardwall)**
(Specification 3624)

Nom. I.D.	⊖	Nom. O.D.	⊖	Max. W.P.	⊕	Suction	⊖	Min. Bend Radius	⤵	Wt. Per Ft.	⚖	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
5/8	15.9	1.00	25.4	150	1.03	30.0	762	6.0	152	.37	.17	Reel	X	3624-0001	
3/4	19.1	1.13	28.7	150	1.03	30.0	762	6.0	152	.42	.19	Reel	X	3624-0002	
1	25.4	1.38	35.1	150	1.03	30.0	762	8.0	203	.57	.26	Reel	X	3624-0003	

RECOMMENDED FOR: Dispensing all types of **commercial gasolines**, or other **petroleum** based products, from service station pumps. A heavy duty **hardwall hose** which does not collapse in reel use or behind the nozzle in heavy duty service.

TEMPERATURE: -40°F to +120°F (-40°C to +49°C) continuous service.

CONSTRUCTION: **Tube:** Type C (Nitrile). Black.
Reinforcement: Braided, high tensile steel wire.
Cover: Type J (CPE). Black. 5/8" and 3/4" smooth, 1" wrapped.
Design Factor: 4:1

COUPLINGS: 24. Reference the Hose Coupling Section.

PACKAGING: 5/8" through 1": Packaged 500' per reel. Maximum 5 pieces. Minimum length 12'.

BRANDING: Continuous transfer label. Example: "GATES® BLACKSNAKE® 3/4 Inch (19.1mm) 1 wire braid (UL) Listed Gasoline Hose Made In U.S.A."

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 5,000 feet per size.

REMNANT LENGTHS: None.

STANDARDS: Underwriters Laboratories Standard No. 330 (USA) and ULC-S612-99 (Canada).
Tube: ARPM (Class A) High oil resistance.